



Multi-WAN Hotspot Gateway Server

Model: WHG1400 Series

(WHG1400-2FP+)

Multi-WAN hotspot gateway router WHG1400 series is designed for IP-based service provider to implement intelligent wireless and wire network access and management. It offers Captive Portal, multi-authentication management system, and supports various enterprise-oriented functions including filter management, intelligent bandwidth management, PPTP/L2TP/IPSec VPN, and multi-WAN.

- 2U rackmount chassis
- 4 x Gbps Ethernet port + 2 x 10Gbps SFP+ (option)
- 3x Hot-Swappable 8038mm (option 1 x 8038mm) Cooling Fans
- EMI Design to resist the electromagnet interference effectively
- Beautiful structure makes your equipment more high-class

WIFI MARKETING PLATFORM (option)

- Wi5ez cloud - Cloud-based hotspot network management
- Wi5ez connect - Local-based hotspot network management

WHG1400 series is a perfect choice to run hotspot businesses. It does not cost a fortune to buy a pile of equipment, nor does it take the skills of an expert to glue multiple applications out of multiple freeware.

WIFI MARKETING PLATFORM

(option)

- Cloud-based hotspot network management - Wi5ez cloud
- Local-based hotspot network management - Wi5ez connect

The router is equipped with great functions on the "Wi5ez cloud" or "Wi5ez connect" wifi marketing platform.

SOME BASIC FEATURES

- Web-based authentication
- RADIUS AAA support
- User authentication and accounting
- Customized Captive Portal
- Create Voucher and QR code for internet connectivity
- User Policy:
 - Share user
 - Session Timeout
 - Timeout for Idle
 - Download / Upload Data Rate
 - Time limit
 - Data limit
- Login by: MAC, Cookie, HTTP CHAP, HTTPS, HTTP PAP, Trial login, MAC Cookie
- Redirect website when connected
- MAC Address Pass-through
- Walled-garden system, access to some web pages without authorization
- Monitor: traffice, hotspot user
- Real-time user status information
-

Please refer to full functions
Wi5ez cloud
Wi5ez connect

SPECIFICATIONS

Model list	
WHG1400-2FP+	4 x Gbps Ethernet port + 2 x SFP+ port
Chassis	2U Rack Mount
HDD	8x 3.5"/2.5" Hot-swappable SAS/SATA3.0 Hard Drives + 2 x 2.5" Hot-Swappable SATA3.0 SSD in rear (Option)
Physical Dimensions	D26.37" x W17.48" x H3.44"
Weight	18 kg (39.68 lbs)
Powering	AC Input Range: 100-240 V
Front Buttons	Power On/Off, System Reset
Environmental Conditions	Operating Temperature: -30°C (-22°F) to 70°C (158°F) Operating Humidity: 10% to 80% non-condensing
Certifications	FCC (United States), CE (Europe) RoHS Compliant

SYSTEM CAPACITY

Concurrent Users	Up to 20,000
On-Demand Accounts	Up to 80,000

NETWORK SERVICES

Internet Protocols Supported: IPv4, IPv6
Static IP, DHCP Server, PPPoE Client, PPPoE Server
Firewall, Routing, NAT, MPLS, Vlan, QoS
VPN Supported: PPTP, L2TP/IPsec, OVPN
WAN Port Load Balancing
Web Proxy
SNMP
IP / MAC / URL Filtering

SYSTEM MANAGEMENT

High Availability
Traffic Network Monitoring
Auto Upgrade
System Health
System Resources
System log
System Backup and Restore
Watchdog

Features and specifications subject to change without notice. Trademarks and registered trademarks are the property of their respective owners.
Copyright ©2021 Wicell Network. Version 2.1/2021

for more details https://www.wicellnetwork.com/product_category/wireless/